
# Hugoniots of Aerogels Involving Carbon and Resorcinol Formaldehyde

J.W. Shon, F.H. Ree, J.A. Viecelli, M. van Thiel, D.A. Young, R.D. Schmidt, L.H. Hrubesh and H.C. Vantine

This paper was prepared for submittal to the

11th Topical Conference of Shocked Compression of Condensed Matter
Snowbird, UT
June 27-July 2, 1999

June 24, 1999



#### DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

## HUGONIOTS OF AEROGELS INVOLVING CARBON AND RESORCINOL FORMALDEHYDE

J. W. Shon, F. H. Ree, J. A. Viecelli, M. van Thiel, D. A. Young, R. D. Schmidt, L. H. Hrubesh, and H. C. Vantine

Lawrence Livermore National Laboratory, P.O. Box 808, Livermore, CA 94550

Abstract. Recently, a first-order phase transition is predicted in liquid carbon using atomistic simulation and Brenner's bond order potential. There are also experimental data suggesting a possibility for a first-order phase transition. In light of this, a thermochemical equilibrium code (CHEQ) is used to provide guidance to experiments to find a liquid-liquid phase change in carbon foam and carbon-rich aerogel, resorcinol formaldehyde. Isotherms and Hugoniots were computed based on the previous analysis by van Thiel and Ree. The present calculations predict the liquid-liquid-graphite triple point to be at 5000 K and 5.2 GPa and its critical point to be at 6000 K and 8.8 GPa. The present Hugoniot calculations suggest that the liquid-liquid phase transition may be detected by performing a shock experiment with initial density of approximately 0.15 gm/cm<sup>3</sup>.

#### INTRODUCTION

A possible presence of a first-order liquid-liquid phase transition in carbon is investigated with a thermochemical equilibrium code (CHEO) which fits theoretical free energy models for the three phases (diamond, graphite, and liquid) to experiments. In 1997 Togaya<sup>3</sup> showed that the slope of pressure-temperature graphite-melting line is discontinuous at the temperature maximum and hence suggested a possible existence of a liquidliquid phase change in carbon. In 1999 Glosli and Ree<sup>2</sup> predicted a first-order phase transition in liquid carbon using atomistic simulation and Brenner's bond order potential. This phase change is associated with density and structural changes. The low-density liquid is predominantly sp bonded with little  $sp^3$  character. The high density liquid is mostly  $sp^3$  bonded with little sp character. Using the CHEQ code<sup>1</sup>, we computed the carbon phase diagram, and Hugoniot, which could provide possible experimental conditions where such a liquid-liquid phase transition could be observed.

#### DESCRIPTION OF CARBON MODEL

A carbon model in CHEQ is developed by van Thiel and Ree<sup>5-7</sup>. The solid phase is modeled by Grüneisen model. The corresponding liquid phase is modeled with Grover's "scaling" model.<sup>8</sup> A modified Lindermann model is used in the scaling theory to predict the melting properties. The liquid carbon consists of a mixture of expanded graphitic and diamond-like forms.

Gibbs free energy of carbon liquid mixture is given by:

$$G_{liq} = xG_d + (1-x)G_g + Rt\{x \ln x + (1-x)\ln(1-x) + A(P,x)\},$$
 (1) with


$$A(P,x) = \left[ \frac{A_o}{1 + (P/P_o)^{1.5}} \right] x(1-x),$$

where x is the atom fraction of diamond liquid, t is the temperature, R is the gas constant, and the


Gibbs free energies of  $G_g$  and  $G_d$  are given in Ref. [5]. The two logarithmic terms are the entropy of mixing and A(P,x) is the strain energy between diamond-like sites and graphitic sites. The functional form of A(P,x) allows a decrease in strain energy as the graphitic sites are compressed and loose their specific symmetry. These coefficient of A(P,x),  $A_o$ , affects the location of the triple and critical points of liquid-liquid phase transition. We have tried a range of value for  $A_o$  from 2.0 to 2.8 and selected  $A_o = 2.4$  for our simulation. When  $A_o$  is 2.0, liquid-liquid phase transition disappears.

#### HUGONIOTS OF CARBON AEROGELS

Hugoniots of carbon foams are computed for initial densities ranging from 0.1 to 1.0 gm/cm<sup>3</sup>. Fig. 1 shows the phase diagram and Hugoniots for carbon foam. The critical temperature of liquidliquid phase transition is located at 6000 K with 8.8 GPa of pressure. The liquid-liquid-graphite triple point is located at 5000 K and pressure of 5.2 GPa. The only Hugoniot that undergoes the liquid-liquid phase transition is the one with initial density of 0.15 gm/cm<sup>3</sup>. This Hugoniot tracks along the graphite-liquid phase transition line, branches out to the liquid-liquid phase transition line, and exits to the liquid phase. The phase diagram is constructed from tracing the phase changes in a series of isotherm calculations by the CHEQ code. The discontinuities in the Hugoniots correspond to the phase transitions.




**FIGURE 1.** Hugoniots of carbon foams with various initial densities. The liquid-liquid-graphite triple point and its critical point are denoted with X. —— represents the phase boundary. —— represents the shock Hugoniots. ( $\rho_0$  is in gm/cm<sup>3</sup>)



**FIGURE 2.** Pressure-density curves for carbon foam with initial densities ranging from 0.1 to 1.0 gm/cm<sup>3</sup>. These curves correspond to Hugoniots in Fig. 1. ( $\rho_o$  is in gm/cm<sup>3</sup>)

Two more figures for carbon foam are obtained from the CHEQ calculations. Fig. 2 shows the pressure-density relations. Under shock compression the carbon can undergo an enormous volume change. This, in turn, produces a large gain in energy and, therefore, high temperature. The sharp horizontal region in the Hugoniot at  $\rho_o = 0.15 \, \text{gm/cm}^3$  is the signature for liquid-liquid phase transition in carbon foam. The sharp horizontal regions for  $\rho_o = 0.15$  and  $1.0 \, \text{gm/cm}^3$  are the signatures for the liquid-liquid and graphite-diamond phase transition, respectively.

The corresponding shock velocity vs. particle velocity is shown in Fig. 3.




**FIGURE 3.** Shock velocity vs. particle velocity for shocking carbon foam. These curves correspond to Hugoniots in Fig. 1.  $(\rho_o \text{ is in gm/cm}^3)$ 

### HUGONIOTS OF RESORCINOL FORMALDEHYDE

Resorcinol fomaldehyde is a carbon-rich organics. Our calculation uses its aerogel with composition C<sub>1</sub>H<sub>0.93</sub>O<sub>0.35</sub> or, by weight %'s of 64.8% carbon, 5.0% hydrogen, 30.0% oxygen. Composition is measured by dynamic flash combustion by Hrubesh. The initial density for resorcinol formaldehyde is about 0.2 gm/cm<sup>3</sup>. The heat of combustion of resorcinol formaldehyde is also measured to be 5326  $\pm$  27 cal/mol from combustion calorimetry experiments by Schmidt. The corresponding heat of formation for resorcinol formadehyde is -216.48 kcal/mol. CHEQ calculations are carried out to obtain the shock Hugoniots and pressure-density relations. The parameter,  $A_o$ , is also chosen to be 2.4. Phase diagram is identical to that of carbon foam, since only carbon undergoes the phase transition for the ranges of interest. But the Hugoniots in Fig. 4 have slightly higher slope from that of pure carbon foam. Hugoniot curve for the initial density of 0.15 gm/cm<sup>3</sup> briefly traces the liquid-liquid phase transition of carbon, as shown in the case of carbon foam.

Fig. 5 shows the pressure-density curves for resorcinol formaldehyde. For low-density aerogel (0.15 gm/cm<sup>3</sup>), the density goes down initially due to high heat release from the compression.



**FIGURE 4.** Shock Hugoniots of resorcinol formaldehyde for initial densities ranging from 0.1 to 1.5 gm/cm<sup>3</sup>. The Hugoniot for the initial density of 1.5 gm/cm<sup>3</sup> undergoes the liquid-liquid phase transition. The discontinuities in Hugoniots represent the presence of the carbon phase transition.




FIGURE 5. Pressure-density curves for resorcinol formaldehyde with initial densities ranging from 0.15 to 1.5 gm/cm<sup>3</sup>.

The discontinuity shown in  $\rho_o = 0.15 \text{ gm/cm}^3$  represents graphite-liquid, and liquid-liquid phase transition. The discontinuity shown in  $\rho_o = 0.3 \text{ gm/cm}^3$  represents the graphite-liquid phase transition. The pressure-density curves for  $\rho_o = 0.6$ -1.5 gm/cm<sup>3</sup> undergo the graphite-diamond phase change at the discontinuities.

#### DISCUSSIONS

Carbon foam and carbon-rich aerogel, resorcinol formaldehyde are investigated for a possible presence of the first order phase transition in liquid carbon. CHEQ calculations predict that the shock Hugoniot experiments for an initial density of 0.15 gm/cm<sup>3</sup> has the best chance for observing the liquid-liquid phase transition.

The critical temperature for the liquid-liquid phase transition sensitively depends on the parameter  $A_o$  of A(P,x) term in the liquid Gibbs free energy expression. At  $A_o = 2.4$ , the critical point is located at 6000 K and 8.8 GPa. The liquid-liquid-graphite triple point is located at 5000 K and 5.2 GPa.

The parameter  $A_o$  is chosen somewhat arbitrary between the values of 2.0 to 2.8. However we currently do not have any experimental evidence to determine  $A_o$  accurately. Therefore, the exact location of the critical temperature for liquid-liquid phase change is still unknown. Experimental effort to determine the liquid-liquid phase transition could clarify this situation.

#### **ACKNOWLEDGMENTS**

This work was performed under the auspices of the U.S. Department of Energy by the Lawrence Livermore National Laboratory under Contract V-7405-ENG-48.

#### REFERENCES

- 1. Ree, F. H., J. Chem. Phys. 81, 1251-1263 (1984).
- 2. Glosli, J. N. and Ree, F. H., *Phys. Rev. Lett.* **82**, 4659-4662 (1999).
- 3. Togaya, M., Phys. Rev. Lett., 79, 2474-2477 (1997).
- 4. van Thiel, M. and Ree, F. H., *J. Appl. Phys.*, 77, 4804-4806 (1995).
- 5. van Thiel, M. and Ree, F. H., *Int. J. of Thermophys.*, **10**, 227-236 (1989).
- van Thiel, M. and Ree, F. H., High Pressure Res., 10, 607-627 (1992).
- van Thiel, M. and Ree, F. H., *Phys. Rev. B*, 48, 3591-3599 (1993).
- 8. Grover, R., J. Chem. Phys. 71, 3824-3829 (1979).